RUGGEDIFED FIELD PG-PDA



European Standards



Lightweight



Wi-F



CDDS



Long Life Battery



Windows

Advantages of the SL-GT Pro

- Lightweight hand held or pole mounted. This data collector unit is under 315gm (11oz) with battery - Carry all day.
- \$\times\$ Sun friendly touch screen 9.4cm (3.7")
- Designed to fit ergonomically in your hand
- Very Affordable \$\$\$

Multi Constellation GNSS

The SL-GT Pro includes advanced multi-constellation receiver, track and navigate with GPS, Glonass, QZSS and SBAS satellites and with future software upgrades also with Galileo and Compass/Beidou satellites. Multi constellation receiver enables you to reach to reliable positions in whatever the environmental condition is.

Highest Standards

Having full VGA (640 x 480 px) 3.7" Sun Readable screen, 5MP Camera, 8 GB of Flash Memory, 806 MHz processor, GSM Voice/Data and waterproof case with IP65 rating makes the SL-GT Pro exclusive in the market.

Industrial Design

Latest technology in the housing material ensures trouble free operation in any conditions in the field. Sun readable and sensitive screen makes it easy to select even very tiny objects from the software package you are using.

Suitable for Every Application

Simply add your desired GIS / GPS software application to the SL-GT Pro and you have a robust, very economical field data capture unit, ready for any outdoor activity.



TECHNICAL SPECIFICATIONS

System Configuration		
System Configuration	Operating System : Windows Mobile 6.5 Processor: 806 Mhz RAM : 256 MB	Internal Flash Memory: 8 GB External Memory: MicroSD card up to 32 GB Screen: 3.7" color touch screen, Full VGA
GPS Features		
	32 channel GPS/GLONASS/GALILEO Support SBAS (WAAS, EGNOS, MSAS)	Single Point Positioning (SBAS) : 1-5 meters
Communication Interface		
	USB Wi-Fi, Bluetooth GSM Voice/Data	Internal 5 megapixel camera MicroSD card slot (upto 32GB)
Power Supply		
	Built-in 3.7V Lithium-lon battery/charger USB Connector	Battery life > 8 hours
Physical Properties	Cina : 15 2 × 0 2 × 2 2 mm	IDCT Waterray of
	Size: 15.2 x 8.2 x 3.2 cm Weight: 315 grams/11oz (with battery) Operating Temperature: -20 C° - + 70 C°	IP65 Waterproof Shock : 1.5 m free fall

STOCKING DEALER

